




さし込み溶接形45°エルボ

SOCKET-WELDING 45° ELBOWS

SW45L

(45° ELBOWS)

JIS B2316



SW45L

UNIT : mm

NOM. SIZE		Sch 80				
(A)	(B)	B	A	D	C	E
8	1/4	23.0	14.3	9.4	10.5	7.9
10	3/8	27.0	17.8	12.7	11.0	7.9
15	1/2	34.0	22.2	16.1	13.0	11.1
20	3/4	39.0	27.7	21.4	14.0	12.7
25	1	47.0	34.5	27.2	16.0	14.3
32	1-1/4	56.0	43.2	35.5	18.0	17.5
40	1-1/2	63.0	49.1	41.2	19.0	20.6
50	2	76.0	61.1	52.7	21.0	25.4
65	2-1/2	96.0	77.1	65.9	27.0	28.6
80	3	109.6	90.0	78.1	31.0	31.8
NOM. SIZE		Sch 160				
(A)	(B)	B	A	D	C	E
15	1/2	39.0	22.2	12.3	14.0	12.7
20	3/4	47.0	27.7	16.2	16.0	14.3
25	1	56.0	34.5	21.2	18.0	17.5
32	1-1/4	63.0	43.2	29.9	19.0	20.6
40	1-1/2	76.0	49.1	34.4	21.0	25.4
50	2	96.0	61.1	43.1	27.0	28.6
65	2-1/2	109.6	77.1	57.3	31.0	31.8

ヤマト特殊鋼株式会社

YAMATO SPECIAL STEEL CO., LTD.

Sheet No. JW-3

平成22年1月5更新